CLAIMS

What is claimed is:

1.   A computer implemented method for creating a translation lookaside
buffer entry comprising:

  a)   accessing a physical memory address associated with a tentative
translation lookaside buffer entry;

  b)   comparing said physical memory address with a predetermined
memory range; and

  c)   if said physical memory address is within said predetermined
memory range, invoking an exception.

2.   The method as described in Claim 1 further comprising modifying said
tentative translation lookaside buffer entry in response to said exception.

3.   The method as described in Claim 2 further comprising storing a modified
translation lookaside buffer entry into a translation lookaside buffer.

4.   The method as described in Claim 1 further comprising if said physical
memory address is outside said predetermined memory range, storing said
tentative translation lookaside buffer entry into a translation lookaside buffer
without modification.

5.   The method as described in Claim 3 further comprising if said physical

memory address is outside said predetermined memory range, storing said

tentative translation lookaside buffer entry into a translation lookaside buffer

5   without said modifying.

6.   The method as described in Claim 1 wherein said tentative translation

lookaside buffer entry is accessed from a page table entry.

10   7.   The method as described in Claim 2 wherein said physical memory

address of said tentative translation lookaside buffer entry is modified by said

modifying.

8.   The method as described in Claim 2 wherein an attribute of said tentative

15   translation lookaside buffer entry is modified by said modifying.

9.   A circuit for creating a translation lookaside buffer entry comprising:

            a fill engine for constructing a tentative translation lookaside buffer

entry and for invoking a comparison between a physical memory address

20   associated with said tentative translation lookaside buffer entry and a

predetermined physical memory address range;

a comparator coupled to said fill engine for comparing said physical memory address associated with said tentative translation lookaside buffer entry and said predetermined physical memory address range and for invoking an exception if a match occurs; and

5   a fix-up handler coupled to said fill engine and said comparator for handling said exception by performing an operation to modify said tentative translation lookaside buffer entry.

10.   The circuit as recited in Claim 9 further comprising a page table entry

10   which provides said tentative translation lookaside buffer entry.

11.   The circuit as described in Claim 9 wherein said fix-up handler generates a modified tentative translation lookaside buffer entry.

15   12.   The circuit as described in Claim 11 wherein said fix-up handler modifies the physical memory address of said tentative translation lookaside buffer entry.

13.   The circuit as described in Claim 11 wherein said fix-up handler modifies an attribute of said tentative translation lookaside buffer entry.

20

14.   The circuit as described in Claim 11 wherein said fill engine enters said modified translation lookaside buffer entry into a translation lookaside buffer.

TRAN-P242/ACM/DAG

15.   A computer system comprising a processor coupled to a bus and a

memory coupled to said bus and comprising instructions that when executed

implement a method of creating a translation lookaside buffer entry comprising:

a)   accessing a physical memory address associated with a tentative

5   translation lookaside buffer entry;

b)   comparing said physical memory address with a predetermined

memory range;

c)   if said physical address is within said predetermined memory

range, invoking an exception.

10

16.   The computer system as described in Claim 15 wherein said method

further comprises modifying said tentative translation lookaside buffer entry in

response to said exception to generate a modified tentative translation lookaside

buffer entry.

15

17.   The computer system as described in Claim 16 wherein said method

further comprises storing said modified tentative translation lookaside buffer entry

into a translation lookaside buffer.

20   18.   The computer system as described in Claim 15 wherein said method

further comprises if said physical address is outside said predetermined memory

range, storing said tentative translation lookaside buffer entry into a translation lookaside buffer without modification.

19.   The computer system as described in Claim 18 wherein if said physical address is outside said predetermined memory range, storing said tentative translation lookaside buffer entry into a translation lookaside buffer without modification.

20.   The computer system as described in Claim 15 wherein said method further comprises obtaining said tentative translation lookaside buffer entry from a page table entry.

21.   The computer system as described in Claim 16 wherein said physical address of said tentative translation lookaside buffer entry is modified by said modifying.

22.   The computer system as described in Claim 16 wherein an attribute of said tentative translation lookaside buffer entry is modified by said modifying.